Hydraulic/Manual Foot Pump Stainless Steel

The HLH Stainless steel lift cart is using SUS304. (The pump is aluminum and the piston is plated iron.) Stainless steel is resistant to water so it can be washed down for a sanitary work area.





MAJOR FEATURES OF THE HLH SERIES

- Hydraulic cylinder
- Swivel casters with brakes
- Foot pedal type
- Comes with an overloading prevention device *1

SPECIFICATIONS

Oil Used

Turbine oil: ISO VG22

Materials

Pump : Aluminum Cylinder : SUS304

Main body: SUS304 (The piston is plated iron)

*1 The lift will not elevate when overloaded.





Load capacity: 330 to 1103 lbs

Unit: inch

	Model	Load capacity	Table dimensions (W × L)	Stroke (ST)	Table height (H to H1)	Overall Length (LL)	Wheels	Number of pump steps	Deadweight
Stainless	HLH-150SUS	330 lbs	15.7"×28.3"	18.9"	9.4" to 28.3"	36.6"	Φ3.9 urethane	22	66.2 lbs
	HLH-250SUS	551 lbs	19.7"×31.5"	21.3"	10.2" to 31.5"	39.9"	Φ3.9 urethane	36	99.2 lbs
	HLH-500SUS	1103 lbs	23.6"×35.4"	23.6"	13.0" to 36.6"	44.1"	Φ5.9 urethane	58	176.4 lbs